

Sofia Touch Panels

Hyper Touch Panel 10" Bluetooth®



10 INCH TOUCH PANEL WITH BLUETOOTH® FOR MANAGING AND CONTROLLING ROOM ACCESS FUNCTIONS



Personalize the user experience in the building

Sofia HyperTouch is a development platform that allows to create personalized experiences inside the building. Displaying a meeting room status, interact with smart locks, show customers relevant information of the building are one of the possibilities with Sofia HyperTouch. We provide the reliable hardware infrastructure that lets you create the application needed for your buildings users.

Product features

- View the status of the rooms in the building.
- Interactions with smart locks.

Sofia Touch Panels Hyper Touch Panel 10" Bluetooth®



DIMENSIONS

Width: 252.9 mm
Height: 169.0 mm
Depth: 22.1 mm

WEIGHT

0.8 kg

MATERIAL

 Technopolymer

COLOUR

 Glossy black

cod. **004S106**

COMMUNICATION INTERFACE

- Bluetooth® Low Energy 5.1
- Ethernet TCP/IP 10/100 base-T
- USB type C
- Dual Band WIFI at 2.4 GHz and 5 GHz

CERTIFICATIONS

- UL/cUL (US); FCC (US); IC (Canada); CE (Europe); CB (International); VCCI, MIC (Japan); RCM (Australia)

Technical features

FIRMWARE

SOFIA

POWER UNIT

AC Input 100-240V AC 50-60Hz

HARDWARE SPECIFICATIONS

Standard Webcam: 8MP, Max Resolution: 1920x1080
Speaker: Standard: 2x 0.8W - Value: 2x 2W
Audio Standard: 2x built-in Digital Microphones - Value: 1x built-in Analog Microphone
8GB SD Card SDCIT/8GBSP
Ports: 1x USB 3.0 support (900mA), Type C USB output, Micro SD slot, GPIO, Ethernet 1x LAN (Gigabit), DC in.

ALERTS

- Led 3-colour series green, red, blue

PRODUCT COMPATIBILITY

Bluetooth 5.0

AES 256 bits encryption

Indoor coverage: approx. 10m*

*The total distance of Bluetooth transmission may vary depending on the location of HyperGate Pro and the surrounding environment. For example, walls, doors, glass surfaces can reduce or interrupt communication between Smart Locks and HyperGate Pro.

MOUNTING

- Wall mounted

WORKING TEMPERATURE

0°C ÷ +40°C

STORAGE TEMPERATURE

-20°C ÷ +50°C

PACKAGE

1 Touch panel 1 Power Supply AC input voltage: 100-240 VAC; Input frequency: 50-60Hz

Compatibility with ISEO applications

ARGO	LUCKEY	LSA	V364
-	•	-	-