

1NCA Smart

Mullion Keyboard 485



CREDENTIAL READER RFID/BLUETOOTH® WITH KEYBOARD, WITH RS485 CONNECTION



A new range of multistandard readers

1NCA Smart Readers is an innovative range of multi-standard, wall-mounted and weatherproof readers of ISEO Connected products line, designed for access management in residential and light commercial buildings. These readers can be easily installed and can manage internal doors but also outdoor gates since they have the IP66 certification.

Elegant in every situation

All 1NCA readers combine sleek and minimalist design with premium and durable materials, which is well suited to different environments. Experience the perfect blend of elegance and reliability, elevating your security measures to new heights and unlocking your freedom to move.

Product features

- Memorize up to 300 users credentials
- Records the last 1000 events
- Wake up by RFID card detection or phone (patented)
- Low energy consumption device
- Real Time Clock/Calendar
- Light and acoustic signals
- Permanently open mode (office mode) without extra battery consumption
- Block the Standard Users allowing access only to VIP users
- Programming and software updates by Argo app on iOS and Android devices




cod. **5E152225**

DIMENSIONS

- Height: 146mm
- Width: 48mm
- Depth: 26mm


MATERIAL

 Technopolymer

FINISH

 Glass

COLOUR

 Glossy black

ACCESS CREDENTIALS

- Badge
- Keyfob
- Bracelet
- Smartphone
- Apple Watch
- Numeric Keypad

COMMUNICATION INTERFACE

- Bluetooth® Low Energy 5.1
- RFID ISO14443B/Mifare ISO14443A
- RS485

CERTIFICATIONS

- Compliance to RED, European and UK directives concerning radio equipment regulations

Technical features

FIRMWARE

ARGO

- Wall mounted

POWER UNIT

9÷24 Vdc (1W) Automatic low power mode max 0,4mW
Internal CR2032 3V Lithium battery for RTC (real time clock) backup

ENVIRONMENTAL FEATURES

- IP66
- H.R. max. 95% without condensing

ALERTS

- Led 3-colour series green, red, blue
- Multi-frequency buzzer

WORKING TEMPERATURE

-20°C ÷ +60°C

STORAGE TEMPERATURE

-20°C ÷ +70°C

PRODUCT COMPATIBILITY

Device with RS485 interface. This reader can be used in the PWW and PWW+R configurations of the Multiblindo Smart lock.

PACKAGE

1 reader, 1 fixing bracket, Torx T8 key, 1 x Fixing bracket
Torx screw (M2,5x5), instruction manual, 2 x Screws (3,5x25 countersunk head) and wall plugs (5x25)

MOUNTING

ACCESSORIES (NOT INCLUDED)

Spacer with screws (cod. 0000IS00354)

Power supply 24Vdc 1.5 A power supply (cod. 5E3506)

Compatibility with ISEO applications

ARGO	LUCKEY	LSA	V364
•	•	-	-