


# 1NCA Smart



Standard Finger

CREDENTIAL READER WITH NUMERIC KEYBOARD, FINGER READER, RFID/BLUETOOTH®, WITH RS485 CONNECTION



## A new range of multistandard readers


1NCA Smart Readers is an innovative range of multi-standard, wall-mounted and weatherproof readers of ISEO Connected products line, designed for access management in residential and light commercial buildings. These readers can be easily installed and can manage internal doors but also outdoor gates since they have the IP66 certification.

## Elegant in every situation

All 1NCA readers combine sleek and minimalist design with premium and durable materials, which is well suited to different environments. Experience the perfect blend of elegance and reliability, elevating your security measures to new heights and unlocking your freedom to move.

## Product features

- Memorize up to 300 users credentials
- Records the last 1000 events
- Wake up by RFID card detection or phone (patented)
- Low energy consumption device
- Real Time Clock/Calendar
- Light and acoustic signals
- Permanently open mode (office mode) without extra battery consumption
- Block the Standard Users allowing access only to VIP users
- Programming and software updates by ARGO App on iOS and Android devices



## DIMENSIONS

- Height: 120 mm
- Width: 82 mm
- Depth: 25,5 mm

## MATERIAL

Technopolymer

## COLOUR

Glossy black

cod. **5E1512355**

## ACCESS CREDENTIALS

- Smartphone
- Apple Watch
- Badge
- Keyfob
- Bracelet
- Numeric Keypad
- Fingerprint

## COMMUNICATION INTERFACE

- Bluetooth® Low Energy 5.1
- RFID ISO14443B/MIFARE ISO14443A
- RS485

## CERTIFICATIONS

- Compliance to RED, European and UK directives concerning radio equipment regulations

## Technical features

### FIRMWARE

ARGO

### POWER UNIT

9÷24 Vdc - Max power consumption = 1W

### ALERTS

- Led 3-colour series green, red, blue
- Multi-frequency buzzer

### PRODUCT COMPATIBILITY

Can be used in combination with ISEO devices with RS485 interface.

### MOUNTING

- Wall mounted

### ENVIRONMENTAL FEATURES

- IP66
- RH 95% max

### WORKING TEMPERATURE

-20°C ÷ +60°C

### STORAGE TEMPERATURE

-20°C ÷ +70°C

### PACKAGE

1 reader, 1 fixing bracket, Torx T8 key, 1 x Fixing bracket Torx screw (M2,5x5), instruction manual, 2 x Screws (3,5x25 countersunk head) and wall plugs (5x25)

### ACCESSORIES (NOT INCLUDED)

Spacer with screws (cod. 0000IS00356)

Power supply 24Vdc 1.5 A power supply (cod. 5E3506)

Compatibility with ISEO applications

---

ARGO	LUCKEY	LSA	V364
•	•	-	-

---