Stylos Smart





ALL-WEATHER CREDENTIAL READER MODULE





A range of credential readers

Stylos Smart is a range of multistandard readers, available in different versions: with and without display and numeric keypad, for indoor and outdoor use. The LED lighting of the device can be customized with three colours.

Can be used with various ISEO solutions

ISEO locks equipped with a Lockbus interface, such as the Thesis 2.0 electro lock, can be connected directly to credential readers without using external actuators, and can also independently manage double gate situations with interlock functions and sign lights.

Product features

- Memorize up to 300 users credentials
- Records the last 1000 events
- Battery-operated device with charge status detection
- Wake up by RFID card detection or phone (patented)
- Low energy consumption device
- Real Time Clock/Calendar
- · Light and acoustic signals
- Block the Standard Users allowing access only to VIP users
- Programming and software updates by Argo app on iOS and Android devices

Stylos Smart All-weather credential reader module



×

cod. 5E1322106

DIMENSIONS

- Width: 47.5mm - Length: 130mm
- Thickness: 17.5mm

FINISH

Technopolymer



ACCESS CREDENTIALS

- Badge
- Keyfob
- Bracelet
- Smartphone
- · Apple Watch

COMMUNICATION INTERFACE

- Bluetooth® Low Energy 5.1
- RFID ISO14443B/Mifare ISO14443A

Technical features

FIRMWARE

ARGO

RELEASE

2.0

POWER UNIT

8÷30 Vdc

ALERTS

- Led 3-colour series green, red, blue
- Multi-frequency buzzer

PRODUCT COMPATIBILITY

To be used with Control Unit 5E0555010

MOUNTING

Wall mounted

ENVIRONMENTAL FEATURES

• IP66

WORKING TEMPERATURE

-20°C ÷ +60°C

STORAGE TEMPERATURE

-25°C ÷ +75°C

PACKAGE

1 reader module with connecting cable, installation sheet, 2 metal screws, 2 plastic screws, 2 fisher adaptors. Note: control unit non included, to be ordered separately.

ACCESSORIES (NOT INCLUDED)

Electric lock actuator (cod. 5E2501)

Plastic back housing for credential reader (cod. 5E0000135)

Electrical jumper. Kit 5 pz (cod. 5E00000205)

Compatibility with ISEO applications

ARGO LUCKEY LSA V364

• - - -