

Aries Smart

For fire locks



ELECTRONIC TRIM RFID/BLUETOOTH® SET FOR FIRE LOCKS



Make your door Smart

The installation flexibility and simplicity make it the perfect solution for community and residential access control (shopping malls, industries, public and private offices, schools and universities, hospitals and retired hostels, residences and hotels, etc.).

For many applications

ARIES electronic trim set can be fit on most doors. It is conceived to be used also with the majority of mechanical locks, for the utmost installation flexibility. The battery operation and cableless technology makes ARIES the perfect solution for access management, ensuring utmost flexibility and low installation costs both on new and existing doors.

Product features

- Handle movement detection.
- Emergency mechanical key detection.
- Privacy signal.
- Memorize up to 300 users credentials
- Records the last 1000 events
- Battery-operated device with charge status detection
- Wake up by RFID card detection or phone (patented)
- Low energy consumption device
- Real Time Clock/Calendar
- Light and acoustic signals
- Permanently open mode (office mode) without extra battery consumption
- Block the Standard Users allowing access only to VIP users
- Programming and software updates by ARGO App on iOS and Android devices

Product options

IP RATING

For internal (IP54) or external (IP55) usage



cod. **00E19x01652**

DIMENSIONS

- Plate width: 38 mm;
- Plate length: 294 mm;
- Plate thickness: 17 mm;
- Handle length: 131 mm from plate center;

WEIGHT

1530 g

FINISH

 Stainless

ACCESS CREDENTIALS

- Badge
- Keyfob
- Bracelet
- Smartphone
- Apple Watch

COMMUNICATION INTERFACE

- RFID ISO14443B/MIFARE ISO14443A
- Bluetooth® Low Energy 5.1

CERTIFICATIONS

- EN 179 certification available in combination with specific locks
- EN 1125 certification available in combination with specific panic devices and locks

Technical features

FIRMWARE

ARGO

RELEASE

2.1

POWER UNIT

2 alkaline batteries 1.5V type AA

ESTIMATED BATTERY LIFE

Up to 2 years, up to 20.000 opening. The figure is dependent on the mode and environment of use and the options activated.

ALERTS

- LEDs: 1 Green, 1 Red
- Multi-frequency buzzer

PRODUCT COMPATIBILITY

Can be fit on any door (wooden, aluminium, metal, PVC and so on).
Door thickness 40 - 85 mm (with standard accessories), 85 - 120 mm (with special accessories).
Suitable for use fire/smoke resisting door assemblies.
7, 8 or 9 (*) mm handle follower. Center distance follower/cylinder 70, 72, 85, 88 and 92 mm.
Backset: 25mm minimum, if using nylon underplate to cover holes on door backset minimum 40mm. European profile cylinder hole.

Latchbolt only or automatic deadbolt function.

Max handle rotation angle 40°.

(*) with adaptor

MOUNTING

- On door

ENVIRONMENTAL FEATURES

- IP54
- IP55 with resistance to salty atmosphere

WORKING TEMPERATURE

-20°C ÷ +60°C

STORAGE TEMPERATURE

-25°C ÷ +75°C

PACKAGE

1 trim, 1 adapter plate kit, 1 handle set, 2 batteries, fastener screws, 2 mm hex key, instruction manual. NOTE: mechanical lock and panic devices not included.

ACCESSORIES (NOT INCLUDED)

Handle follower and screws set (mandatory)
Override cylinder
Override keys set
Underplate

Lock

Compatibility with ISEO applications

ARGO	LUCKEY	LSA	V364
•	•	-	-
