# **1NCA** Smart

## Mullion Keyboard Relay



CREDENTIAL READER WITH KEYBOARD, RFID CONTACTLESS MULTISTANDARD, BLUETOOTH®, WITH BUILT IN RELAY.





# A new range of multistandard readers

1NCA Smart Readers is an innovative range of multi-standard, wall-mounted and weatherproof readers of ISEO Connected products line, designed for access management in residential and light commercial buildings. These readers can be easily installed and can manage internal doors but also outdoor gates since they have the IP66 certification.

# Elegant in every situation

All 1NCA readers combine leek and minimalist design with premium and durable materials, which is well suited to different environments. Experience the perfect blend of elegance and reliability, elevating your security measures to new heights and unlocking your freedom to move.

## Product features

- Memorize up to 300 users credentials
- Records the last 1000 events
- Wake up by RFID card detection or phone (patented)
- Low energy consumption device
- Real Time Clock/Calendar
- · Light and acoustic signals
- Permanently open mode (office mode) without extra battery consumption
- Block the Standard Users allowing access only to VIP users
- Programming and software updates by Argo app on iOS and Android devices

# **1NCA** Smart Mullion Keyboard Relay






#### **DIMENSIONS**

- Height: 146mm - Width: 48mm
- Depth: 26mm

## **FINISH**





cod. 5E152425

#### **ACCESS CREDENTIALS**

- Badge
- Keyfob
- Bracelet
- Smartphone
- · Apple Watch

#### **COMMUNICATION INTERFACE**

- RFID ISO14443B/Mifare ISO14443A
- Bluetooth® Low Energy 5.1

#### **CERTIFICATIONS**

 Compliance to RED, European and UK directives concerning radio equipment regulations

Technical features

#### **FIRMWARE**

**ARGO** 

#### **POWER UNIT**

9÷24 Vdc (1W) Automatic low power mode max 0,4mW Internal CR2032 3V Lithium battery for RTC (real time clock) backup

### **ALERTS**

- Led 3-colour series green, red, blue
- Multi-frequency buzzer

#### **MOUNTING**

Wall mounted

#### **ENVIRONMENTAL FEATURES**

- IP66
- H.R. max. 95% without condensing

## **WORKING TEMPERATURE**

-20°C ÷ +70°C

#### STORAGE TEMPERATURE

-25°C ÷ +75°C

## **PACKAGE**

1 reader, 1 fixing bracket, Torx T8 key, 1 x Fixing bracket Torx screw (M2,5x5), instruction manual, 2 x Screws (3,5x25 countersunk head) and wall plugs (5x25).

## **ACCESSORIES (NOT INCLUDED)**

Spacer with screws (cod. 0000IS00354)
Power supply 24Vdc 1.5 A power supply (cod. 5E3506)

COHIDAUDIII WILLI ISEO ADDIICAUDI	with ISEO applications	Compatibility
-----------------------------------	------------------------	---------------

ARGO	LUCKEY	LSA	V364
•	•	-	-