
Gateways

V364 Gateway



Version P.O.E. (Power Over Ethernet)

THE GATEWAY OPERATES AS F9000 VALIDATOR FOR THE F9000 ON KEYS IN ITS BLUETOOTH RANGE (AROUND 10 METERS DEPENDING ON ENVIRONMENT CONDITIONS).






Validate your F9000 key via Bluetooth smart

The V364 Gateway operates as validator for the F9000 ON keys. It communicates with the Atlas Master (V364 Classic) or Virtual Atlas Master (V364 on air or V364 Customer Hosted) with data connection and towards the F9000 ON keys with Bluetooth Smart. The V364 Gateway can validate all the F9000 ON keys in its Bluetooth range (around 10 meters depending on environment conditions).

Product features

- "Desktop" format with the possibility of wall mounting
- Data conversion (WIFI or Ethernet) to Bluetooth®





DIMENSIONS

- Width: 125mm - Depth: 40mm - Height: 85mm

MATERIAL Technopolymer

COLOUR White

cod. 5E072514

Technical features

FIRMWARE

1RIS

POWER UNIT

Requires PoE Switch IEEE 802.3af up to 15,4W. Delivery of data and power over CAT5e/CAT6 ethernet cable. Maximum power consumption 10W.

HARDWARE SPECIFICATIONS

ARM A7 based CPU module 512 MB RAM 8 GB Flash eMMC Non volatile Memory

OPERATING SYSTEM

Embedded Linux

PRODUCT COMPATIBILITY

Compatible with ISEO F9000 ON keys

WORKING TEMPERATURE

0°C ÷ +50°C

STORAGE TEMPERATURE

-25°C ÷ +75°C

PACKAGE

1 Gateway PoE

ACCESSORIES (NOT INCLUDED)

Wall fixing brackets kit (code 0000A00154)

Compatibility with ISEO applications

ARGO	LUCKEY	LSA	V364
-	•	•	•