

Credential reader with led

CREDENTIAL READER WITH LED



A range of credential readers

Stylos is a range of multistandard readers, available in different versions: with and without display and numeric keypad, for indoor and outdoor use. The LED lighting of the device can be customized with three colours.

Can be used with various ISEO solutions

ISEO locks equipped with a Lockbus interface, such as the Thesis 2.0 electro lock, can be connected directly to credential readers without using external actuators, and can also independently manage double gate situations with interlock functions and sign lights.

Product features

- Wake up by RFID card detection or phone (patented)
- Battery-operated device with charge status detection
- Low energy consumption device
- Credential reader/validator when connected to the Atlas controller
- Software updatable on site via Bluetooth® phone (Stand Alone) or from Atlas controller (online)
- Real Time Clock/Calendar
- Light and acoustic signals

Stylos Credential reader with led



cod. **5E1320126**

DIMENSIONS

- Width: 47.5mm
- Length: 130mm
- Thickness: 17.5mm

Technical features

FIRMWARE

1RIS

-25°C ÷ +75°C

RELEASE

2.0

PACKAGE

1 reader, instruction manual, 2 screws for metal, 2 screws for plastic, 2 fisher adaptors.

WORKING TEMPERATURE

-20°C ÷ +60°C

ACCESSORIES (NOT INCLUDED)

Electric lock actuator (code 5E2501)
Plastic back housing for credential reader (code 5E0000135)
Electrical jumper. Kit 5 pz (code 5E00000205)

STORAGE TEMPERATURE

Compatibility with ISEO applications

ARGO	LUCKEY	LSA	V364
-	•	•	•